

Package: toxSummary (via r-universe)

September 12, 2024

Title Visualize and Summarize Repeat-Dose Toxicology Study Results

Version 1.0.0

Description 'shiny' app that generates plots and summary tables from repeat-dose toxicology study results to facilitate holistic evaluation of the drug safety of active pharmaceutical ingredient (API) prior to initiation of clinical trials.

License MIT + file LICENSE

URL <https://github.com/phuse-org/toxSummary>

BugReports <https://github.com/phuse-org/toxSummary/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

Imports cicerone, data.table, DBI, dplyr, DT, flextable, fs, ggiraph, ggplot2, htmltools, magrittr, patchwork, rlang, RSQLite, scales, shiny, shinycssloaders, shinydisconnect, stringr

Depends R (>= 2.10)

Suggests knitr, officer, rmarkdown

VignetteBuilder knitr

Repository <https://phuse-org.r-universe.dev>

RemoteUrl <https://github.com/phuse-org/toxsummary>

RemoteRef HEAD

RemoteSha f3a915977d62593bb658c0904c8eb1fc62fa4a5a

Contents

toxSummary_app	2
Index	3

toxSummary_app	<i>Run toxSummary app</i>
----------------	---------------------------

Description

Run toxSummary app

Usage

```
toxSummary_app(  
  database_path = NULL,  
  studyid_file = NULL,  
  save_file_path = NULL,  
  where_to_run = "local"  
)
```

Arguments

database_path	Optional, character file path for database
studyid_file	Optional, character file path for studyid
save_file_path	Optional, character path where file will be saved when app create any files. If NULL, file will be saved in current working directory
where_to_run	Optional, character where app will be running. Default is "local". Should use "rsconnect" when deploy to rsconnect.

Value

function run the app.

Examples

```
## Not run:  
toxSummary_app()  
  
## End(Not run)
```

Index

toxSummary_app, [2](#)